TIRUPATI™
INTERNATIONAL

www.tpaper.in

Dye Sublimation Printer

(8 HEADS)

Production

1 PASS - 4800 Mtrs/Day



Tx-08

C M Y K

Sublimation Ink

08*i3200 Heads
CMYK



360 x 1200 Dpi - 1pass	320m2/h
360 x 2400 Dpi - 2pass	180m2/h
360 x 3600 Dpi - 3pass	120m2/h

www.tpaper.in

Both the sublimation and direct-to-textile printers are examples of our expertise and engineering top performing, reliable and precise. With the TIRUPATI series printer, you can maximize productivity while controlling quality and minimizing cost for beautiful soft signage, apparel, and interior decor items that will set your business apart from the competition. Wide application in clothing, home decoration fabric, samplings, shirt canvas bags, bolster scooter, flags, textile gadgets, etc.




Double high-precision mute rail

Stable 5L bulk system ensures amazing printing speed


Front expander

Rear media balance bar

Media retraction tension bar

Jombomedia roll maximum 1000m media load

Inflatable take up and feed media shaft

Frequency motor ensures more stable material loading and take-up

TECHNICAL SPECIFICATIONS

Model		TX-08
Print Head		08*i3200 Print Heads
Printing Technology		Piezoelectric Inkjet
Acceptable Media	Width	71.6 in.(1820 mm)
	Thickness	Maximum 39 mil(1 mm)
	Weight	220 lb.(100 kg)
Printing Width		70.8 in.(1800 mm)
Ink Cartridges	Type	Dye Sublimation Ink
	Capacity	4*4 CISS (220ml ink cartridge with 5L ink tank)
	Color	4 colors (Cyan, Magenta, Yellow, Black)
RIP Software		Neostampa 8.9
Printing Resolution		Maximun 2400 dpi
Printing Speed		1 pass(360x1200dpi): 320 sqm/h 3pass(360x2400dpi): 180 sqm/h 3pass(360x3600dpi): 120 sqm/h
Media Heating System		Intergrated post heater & Infrared Dryer & Fan system
Interface		USB 3.0
Power Supply		AC 220V+ 10%, 50/60 HZ
Dimensions(with stand)		133.86(W)x51.18(D)x74.80(H) in. (3400(W)x1300(D)x1900(H)mm)
Weight(with stand)		1212.54 lb. (550 kg)
Package Dimensions		133.86(W)x55.12(D)x78.74(H)in. (3600(W)x1400(D)x2000(H)mm)
Package Weight		1455.05 lb.(660kg)
Environment	Power off	Temperature: 59 *F to 90 *F [15'C to 32 'C] / Humidity: 35 to 80% (no condensation)
	Power off	Temperature: 41 *F to 104 *F [5'C to 40 'C] / Humidity: 20 to 80% (no condensation)
Accessories		USB cable, media clamp, manual, drain bottle, ink cartridges, RIP software etc.

CONTACT US

Mr. Kalpesh
+91 82384 33322

Mr. Ravi
+91 75729 33322

Mr. Nikunj
+91 99788 00900

sublimation@tpaper.in

Mr. Kishan
+91 75738 33322

Mr. Harsh
+91 99788 12212

PLOT NO - 2, T.P - 48 OPP. SAI UNITY RAW HOUSE, NEAR S.M.C SCHOOL,
BHESTAN, SURAT - GUJARAT - INDIA - 395023